

TITANIUM 11mm

With stitched ends




**SUPER STRONG AND WEAR RESISTANT 11MM STATIC ROPE
will MEET THE DEMAND of ANY RIGGER.**

Supplied with STRONG STITCHED loop AT EACH END.

Available in 9 different LENGTHS: 5, 10, 15, 20, 25, 30, 40, 50, 60 METRES.

CE
EN1891A

Ref. code	LENGTH
1900.5	5 M
1901	10 M
1901.5	15 M
1902	20 M
1902.5	25 M
1903	30 M
1904	40 M
1905	50 M
1906	60 M



TITANIUM 11 - TECHNICAL DATA

Diameter	Static strength	Strength with Figure 8 Knot	Number of Factor 1 Falls	Impact Force Factor 0.3	Elongation 50/150 kg	Sheath slippage	Weight (g/m)	Sheath Percentage	Shrinkage in Water	Material
11 mm	2900 daN (kg)	2050 daN (kg)	15 (100 kg.)	5,60 kN	2,8%	0,8 %	73 g.	36 %	4 %	Polyamide

**High strength
polyamid stitchings.
Breaking load 22kN.**

**PROTECTIVE
METAL THIMBLE**

**ABRASION RESISTANT
plastic PROTECTION
layer.**

27/04/2010